

CS 252:

Advanced Programming Language Principles



ES6 JavaScript, Metaprogramming, & Object Proxies

Prof. Tom Austin

San José State University

HW4 Review

Fixing JavaScript

- ECMAScript committee formed to carefully evolve the language.
 - "Don't break the web."
- Involved big players in JS world:
 - Google, Microsoft, Apple, Mozilla, Adobe, and many more

ECMAScript Schism

- ECMAScript 4 was divisive
- A group broke off to create ECMAScript 3.1
 - more minor updates
 - later became ECMAScript 5
- Adobe left the fold

Strict Mode

- Turns anti-patterns into errors:
 - Variables must be declared.
 - Using `with` not allowed.
 - Many others.
- To use, add `"use strict";` (including quotes) to the top of your function or file.
 - Why in a string?

Forget var, variables are global

```
function swap(arr,i,j) {
  tmp = arr[i]; arr[i] = arr[j]; arr[j] = tmp;
}
function sortAndGetLargest (arr) {
  tmp = arr[0]; // largest elem
  for (i=0; i<arr.length; i++) {
    if (arr[i] > tmp) tmp = arr[i];
    for (j=i+1; j<arr.length; j++)
      if (arr[i] < arr[j]) swap(arr,i,j);
  }
  return tmp;
}
var largest =
sortAndGetLargest([99,2,43,8,0,21,12]);
console.log(largest); // should be 99, but prints 0
```

But with "use strict", the error is detected.

```
"use strict";
function swap(arr,i,j) {
    tmp = arr[i]; arr[i] = arr[j]; arr[j] = tmp;
}
function sortAndGetLargest (arr) {
    tmp = arr[0]; // largest elem
    for (i=0; i<arr.length; i++) {
        if (arr[i] > tmp) tmp = arr[i];
        for (j=i+1; j<arr.length; j++)
            if (arr[i] < arr[j]) swap(arr,i,j);
    }
    return tmp;
}
var largest =
sortAndGetLargest([99,2,43,8,0,21,12]);
console.log(largest); // should be 99, but prints 0
```

```
$ node sort.js
```

```
/Users/taustin/temp/sort.js:6  
  tmp = arr[0]; // largest elem  
    ^
```

```
ReferenceError: tmp is not defined
```

```
  at sortAndGetLargest (/Users/taustin/temp/sort.js:6:7)  
  at Object.<anonymous> (/Users/taustin/temp/sort.js:14:15)  
  at Module._compile (module.js:652:30)  
  at Object.Module._extensions..js (module.js:663:10)  
  at Module.load (module.js:565:32)  
  at tryModuleLoad (module.js:505:12)  
  at Function.Module._load (module.js:497:3)  
  at Function.Module.runMain (module.js:693:10)  
  at startup (bootstrap_node.js:191:16)  
  at bootstrap_node.js:612:3
```

```
$
```

ES6 Harmony: Can't we all just get along?

- ECMAScript 6 (ES6) Harmony
 - Later renamed ECMAScript 2015
- New features:
 - classes
 - block scoping
 - arrow functions (lambdas)
 - promises
 - proxies

let is the new var

```
function makeListOfAdders(lst) {  
  var arr = [];  
  for (var i=0; i<lst.length; i++) {  
    var n = lst[i];  
    arr[i] = function(x) { return x + n; }  
  }  
  return arr;  
}
```

```
var adders =  
  makeListOfAdders([1, 3, 99, 21]);  
adders.forEach(function(adder) {  
  console.log(adder(100));  
});
```

Prints:

121

121

121

121

```
function makeListOfAdders(lst) {  
  let arr = [];  
  for (let i=0; i<lst.length; i++) {  
    let n = lst[i];  
    arr[i] = function(x) { return x + n; }  
  }  
  return arr;  
}
```

```
var adders =  
  makeListOfAdders([1, 3, 99, 21]);  
adders.forEach(function(adder) {  
  console.log(adder(100));  
});
```

Prints:

101

103

199

121

Arrow functions

- Concise function syntax
- `this` bound lexically
 - Normal functions bind `this` dynamically.

```
function sort (lst, fn) {
  for (let i=0; i<lst.length; i++) {
    for (let j=0; j<lst.length-1; j++) {
      if (fn(lst[i], lst[j])) {
        let tmp = lst[i];
        lst[i] = lst[j];
        lst[j] = tmp;
      }
    }
  }
}
```

```
let arr = [1,2,99,10,42,7,-3,88,6];
sort(arr, function(x,y) { return x<y; });
```

```
function sort (lst, fn) {
  for (let i=0; i<lst.length; i++) {
    for (let j=0; j<lst.length-1; j++) {
      if (fn(lst[i], lst[j])) {
        let tmp = lst[i];
        lst[i] = lst[j];
        lst[j] = tmp;
      }
    }
  }
}
```

```
let arr = [1,2,99,10,42,7,-3,88,6];
sort(arr, (x,y) => x<y);
```

A broken JavaScript constructor

```
function Rabbit(name, favFoods) {  
  this.name = name;  
  this.myFoods = [];  
  favFoods.forEach(function(food) {  
    this.myFoods.push(food);  
  });  
}
```

this refers to
the global scope

```
var bugs = new Rabbit("Bugs",  
  ["carrots", "lettuce", "souls"]);  
console.log(bugs.myFoods);
```

this bound lexically with arrows

```
function Rabbit(name, favFoods) {  
  this.name = name;  
  this.myFoods = [];  
  favFoods.forEach((food) =>  
    this.myFoods.push(food);  
  );  
}
```

Now this
refers to the
new object

```
var bugs = new Rabbit("Bugs",  
  ["carrots", "lettuce", "souls"]);  
console.log(bugs.myFoods);
```

Promises

- Promise: an object that *may* produce a value in the future.
- Similar to listeners, but
 - can only succeed or fail once
 - callback is called even if event took place earlier
- Simplify writing asynchronous code

Promise states

- Fulfilled (resolved)
- Rejected
- Pending

```
let fs = require('fs');
let p = new Promise((resolve, reject) => {
  // { key: 'hello' }
  let f = fs.readFileSync('./test.json');
  resolve(f);
});

p.then(JSON.parse)
  .then((res) => res.key)
  .then((res) => console.log(res + " world!"));
```

```
let fs = require('fs');
let p = new Promise((resolve, reject) => {
  // { key: 'hello' }
  let f = fs.readFileSync('./test.json');
  resolve(f);
});

p.then(JSON.parse)
  .then((res) => res.key,
    (err) => console.error(err))
  .then((res) => console.log(res + " world!"));
```

Proxies

What is *metaprogramming*?

Writing programs
that manipulate
other programs.

JavaScript Proxies

Metaprogramming feature proposed
for ECMAScript 6 (Harmony).

Proposed
By:



Tom Van
Cutsem

Mark Miller



Proxies: Design Principles for Robust Object-oriented Intercession APIs

Abstract: Proxies are a powerful approach to implement meta-objects in object-oriented languages without having to resort to metacircular interpretation. We introduce such a meta-level API based on proxies for Javascript...

Metaprogramming terms

- **Reflection**
 - **Introspection**: examine a program
 - **Self-modification**: modify a program
- **Intercession**: redefine the semantics of operations.
- Reflection is fairly common.
Intercession is more unusual.

Introspection

Ability to examine the structure of a program.

In JavaScript:

```
"x" in o;  
for (prop in o) { ... }
```



Property
lookup

Property
enumeration

Self-modification

Ability to modify the structure of a program.

```
o["x"]; // computed property  
o.y = 42; // add new property  
delete o.x; // remove property  
o["m"].apply(o, [42]);  
// reflected method call
```

Until recently, JavaScript did not support intercession.

JavaScript proxies are intended to fix that.

But first a little history...

Common Lisp

- Developed before object-oriented languages were popular.
- Many libraries were created with non-standard OO systems.

Common Lisp Object System (CLOS)

- Became standard object-oriented system for Lisp
- *What could be done about pre-existing object-oriented libraries?*

The Devil's Choice

1. Rewrite libraries for CLOS?

- huge # of libraries
- infeasible to rewrite them all

2. Make complex API?

- difficult API to understand.
- Systems had conflicting features...
- ...But were essentially doing the same things.



Gregor Kiczales chose option 3:



- Keep API simple.
- Modify object behavior to fit different systems.

Metaobject protocols were born...

JavaScript Object Proxies

Intercession API

Proxy and handler

The behavior of a *proxy* is determined by *traps* specified in its *handler*.



The metaobject

What kind of things do we
want to do to an object?

No-op forwarding proxy

No-op handler:
All ops forwarded to
target without change

```
var target = {};  
var p = new Proxy(target, {});  
p.a = 37; // op forwarded  
console.log(target.a); // 37.
```

Available traps

- has
- get
- set
- deleteProperty
- apply
- construct
- getOwnPropertyDescriptor
- getPrototypeOf
- setPrototypeOf
- isExtensible
- preventExtensions
- defineProperty
- ownKeys

Another use case for proxies

- Share a reference to an object, but do not want it to be modified.
 - Reference to the DOM, for instance
- We can modify the forwarding handler to provide this behavior:

Read-only handler

```
let roHandler = {
  deleteProperty: function(t, prop) { return false;},
  set: function(t, prop, val, rcvr) { return false;},
  setPrototypeOf: function(t,p) { return false; } };

var constantVals = {
  pi: 3.14,
  e: 2.718,
  goldenRatio: 1.30357 };

var p = new Proxy(constantVals, roHandler);
console.log(p.pi);
delete p.pi;
console.log(p.pi);
p.pi = 3;
console.log(p.pi);
```

Safe constructor handler

```
function Cat(name) {
  this.name = name;
}
Cat = new Proxy(Cat, {
  apply: function(t, thisArg, args) {
    throw Exception("Forgot new");
  }
});
var g = new Cat("Garfield");
console.log(g.name);
var n = Cat("Nermal");
```



Forgot new:
exception raised

Undoable object

get, set, delete trap example
(in class)

Aspect-oriented programming (AOP)

- Some code not well organized by objects
 - *Cross-cutting concern*
- Canonical example: logging statements
 - littered throughout code
 - Swap out logger = massive code changes

Lab: Tracing API

- Use proxies to log all actions taken on an object
 - Override `has`, `get`, `set`, `apply`, `construct`, & `deleteProperty`
- Avoids having complexity of logging framework
- **No starter code for this assignment**